

Quick Start - Link to EziWeigh7

QS

Tru-Test EziWeigh7

- ▷ links to the Shearwell stock recorder - no pairing code
- ▷ links to SDL 400 red stick reader - no pairing code
- ▷ links to SDL440 blue stick reader - no pairing code

Link to a stock recorder for SDL crates

- » On the stock recorder - open the Bluetooth Manager
- » **Scan** to locate the signal from the EziWeigh.
- » Highlight **EziWeigh** and tap **Pair**. On the Authentication screen leave the passcode blank. Tap **Next**.
- » Choose a BSP port and tap **Done**.
- » In FarmWorks, go to **Options > Weigher**
- » Select **Tru-Test**; use the buttons to select the correct BSP port. Test the connection.
- » Escape to sheep or cattle procedures to start weighing.

QS

Link to a red (SDL400) or blue (SDL440) stick reader

Shearwell red and blue stick readers both link to EziWeigh7. Tag numbers and weights are saved in a file on the weigher. The weigher connects to a PC with the USB power cable; data is transferred using Tru-Test EziLink software, a free program from Tru-Test. Tag and weight data can then be saved as a text file or an Excel spreadsheet.

- » Find the Bluetooth address of the weigher. It will either be on a sticker on the back, or go into **Menu > Setups** and scroll down till you find the BT address.
- » Open SDL Connect on your computer and connect to your stick reader.
- » Click on **Configure Stick**.
- » Scroll down to find the **Weigher Bluetooth ID** field. Type in the Bluetooth ID number for your weigher. Click **Save Configuration** and **Quit**.
- » On a Mac computer, click on **Peripherals** and make the same changes. Click **Save**.
- » On the EziWeigh7 push the **Menu** button. Use the down arrow to move to Setups. Press **Enter**.
- » Use the down arrow to move to **Auto Record**. Press the Enter button to select **Auto Record with ID**. Press the **Esc** button twice to exit.

QS

Tips for using an EziWeigh7

1. Tag files can be uploaded using the computer software (EziLink)
2. **Auto Record with ID** means it will save the record as long as there is an EID. **Auto Record without ID** means just the weight is saved.
3. **Record IDs Immediately** (on or off) means the EID is saved, even if the animal isn't weighed.
4. Damp System should be set to **Super Damp III (cattle)** - it is the most accurate and should be the default. Super Damp III (sheep) is for fast weighing but is less accurate.

Quick Start - Link to EziWeigh7i

QS

Tru-Test EziWeigh7i

- ▷ links to the Shearwell stock recorder - pairing code 0000
- ▷ links to SDL440 blue stick reader - Set EID Output to Full ISO

Link to a stock recorder for SDL crates

- » On the EziWeigh7i, in **Menu > Setups**, set **Auto Record** to **Off**.
- » On the stock recorder - open the Bluetooth Manager
- » **Scan** to locate the signal from the EziWeigh.
- » Highlight **EziWeigh** and tap **Pair**. On the Authentication screen enter the passcode 0000. Tap **Next**.
- » Choose a BSP port and tap **Done**.
- » In FarmWorks, go to **Options > Weigher**
- » Select **Tru-Test**; use the buttons to select the correct BSP port. Test the connection.
- » Escape to sheep or cattle procedures to start weighing.

QS

Link to blue (SDL440) stick reader

Shearwell blue stick readers link to EziWeigh7i. Tag numbers and weights are saved in a file on the weigher. The weigher connects to a PC with the USB power cable; data is transferred using Tru-Test EziLink software, a free program from Tru-Test. Tag and weight data can then be saved as a text file or an Excel spreadsheet.

- » Find the Bluetooth address of the weigher. It will either be on a sticker on the back, or go into **Menu > Setups** and scroll down till you find the BT address.
- » Open SDL Connect on your computer and connect to your stick reader.
- » Click on **Configure Stick**.
- » Set the **EID Output Format** to **Decimal** (or anything except UK WYSIWYG)
- » Scroll down to find the **Weigher Bluetooth ID** field. Type in the Bluetooth ID number for your weigher. Click **Save Configuration** and **Quit**.
- » On a Mac computer, click on **Peripherals** and make the same changes. Click **Save**.
- » Turn on your stick reader by holding down the green button. Release the button when **Link to Weigher** appears. The blue light on the stick will glow when a Bluetooth link is made.
- » On the EziWeigh7 push the **Menu** button. Use the down arrow to move to Setups. Press **Enter**.
- » Use the down arrow to move to **Auto Record**. Press the Enter button to select **Auto Record with ID**. Press the **Esc** button twice to exit.

QS

Tips for using an EziWeigh7i

1. Does NOT link to a red stick reader
2. EID Output Format must be set to anything besides UK WYSIWYG
3. Tag files can be uploaded using the computer software (EziLink)
4. **Auto Record with ID** means it will save the record as long as there is an EID. **Auto Record without ID** means just the weight is saved.
5. **Record IDs Immediately** (on or off) means the EID is saved, even if the animal isn't weighed.
6. Damp System should be set to **Super Damp III (cattle)** - it is the most accurate and should be the default. Super Damp III (sheep) is for fast weighing but is less accurate.